

SAFETY DATA SHEET

Issuing Date 19-Mar-2018

Revision Date 03-Nov-2020

Revision Number 3

This document complies with the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier	
Product Name	Activator 9000
Other means of identification	
Synonyms	DuraShield 210 Part B-Iso; DuraShield 210-61 Part B-Iso; DuraShield 215 Part B-Iso; DuraShield 310 Part B-Iso; DuraShield 310-61 Part B-Iso; DuraShield 320 Part B-Iso
Recommended use of the chemica	al and restrictions on use
Recommended Use	Activator for Curing Chemical Resistant Coating
Uses advised against	Consumer use
Supplier's details	
Initial Supplier Cloverdale Paint Inc. 400-2630 Croydon Drive Surrey, British Columbia V3Z 6T3	
Manufacturer Address LifeLast. Inc. 3813 Helios Way Suite 190 Pflugerville, TX 78660 Telephone number: 512-628-2112 Emergency telephone number	
Emergency Telephone Number	Chemtrec 1-800-424-9300
	2. HAZARDS IDENTIFICATION
Classification	

This product is considered hazardous according to the criteria set within the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

Acute Inhalation Toxicity - Dusts and Mists	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Respiratory Sensitization	Category 1
Skin Sensitization	Category 1
Carcinogenicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3

Category 2

Label Elements

Signal Word Danger



Hazard Statements Harmful if inhaled Causes skin irritation Causes serious eye irritation May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction Suspected of causing cancer. May cause respiratory irritation May cause damage to organs through prolonged or repeated exposure

Physical and Health Hazards Not Otherwise Classified Not applicable.

Precautionary Statements

Prevention

- · Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash face, hands and any exposed skin thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- · Contaminated work clothing should not be allowed out of the workplace.
- Wear protective gloves/protective clothing/eye protection/face protection.
- In case of inadequate ventilation wear respiratory protection.

General Advice

· If exposed or concerned: Get medical attention/advice

Eyes

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina.

• If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- Take off contaminated clothing and wash before reuse.
- If skin irritation or rash occurs: Get medical advice/attention.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Storage

- · Store locked up.
- · Store in a well-ventilated place. Keep container tightly closed.

Disposal

· Dispose of contents/container to an approved waste disposal plant.

Other information

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

DuraShield 210 Part B-Iso; DuraShield 210-61 Part B-Iso; DuraShield 215 Part B-Iso; DuraShield 310 Part B-Iso; DuraShield 310-61 Part B-Iso; DuraShield 320 Part B-Iso

Chemical Name	CAS-No	Weight %	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Polymethylene polyphenylene isocyanate	9016-87-9	60-100	-	-
4,4-Methylenediphenyl diisocyanate	101-68-8	30-60	-	-

4. FIRST AID MEASURES

Description of necessary first-a Eye Contact	id measures IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.		
Skin Contact	Wash skin with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Remove and wash contaminated clothing before re-use.		
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.		
Ingestion	IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.		
Most important symptoms/effects, acute and delayed			
Most Important Symptoms/Effects	Asthma-like and/ or skin allergy-like symptoms. Rashes. Irritation.		
Indication of immediate medical att	Indication of immediate medical attention and special treatment needed, if necessary		
Notes to Physician	May cause sensitization by inhalation and skin contact.		
5. FIRE-FIGHTING MEASURES			
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Unsuitable Extinguishing Media	Water.		
Specific Hazards Arising from the Chemical	Closed container may forcibly rupture under extreme heat or when contents are contaminated with water. Use cold-water spray to cool fire-exposed containers to minimize the risk of rupture. Large fires can be extinguished with large volumes of water applied from a safe distance, since reaction between water and hot isocyanate can be vigorous.		
Explosion Data Sensitivity to Mechanical Impac Sensitivity to Static Discharge	t None. None.		
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.		

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists.
Environmental Precautions	
Environmental Precautions	Prevent further leakage or spillage if safe to do so. See Section 12 for additional Ecological Information. Prevent entry into waterways, sewers, basements or confined areas.
Methods and materials for containm	ent and cleaning up
Methods for Containment	Dike far ahead of liquid spill for later disposal.
Methods for Cleaning Up	Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Use personal protective equipment. Do not fill the container more than 2/3 full to allow for expansion, and do not tighten the lid on the container. Repeat application of absorbent material until all the liquid has been removed from the surface.
	Collect material in open-head metal containers. Repeat applications of decontamination solution, with scrubbing, followed by absorbent material until deconatiminated. Check for residual contamination. Swype test kits have been used for this purpose. Apply lid loosely and allow containers to vent for 72 hours to let carbon dioxide escape.
	 Neutralizing solutions: 1) Colorimetric Laboratories Inc. (CLI) decontamination solution 2) A mixture of 75% water, 20% non-ionic surfactant (e.g. Poly-tergent SL-62, Tergitol TMN-10) and 5% n-propanol. 3) A mixture of 80% water and 20% non-ionic surfactant. 4) mixture of 90% water, 3 - 8% ammonium hydroxide or concentrated ammonia, and 2% liquid detergent.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling	Obtain special instructions before use. Do not handle until all safety precautions have beer read and understood. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Wash thorough after handling. Use only in ventilated areas. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/fac protection. In case of insufficient ventilation, wear suitable respiratory equipment.	
Conditions for safe storage, including any incompatibilities		
Storage	Store locked up. Store in a well-ventilated place. Keep cool.	
Incompatible Products	Water, Strong oxidizing agents, Strong bases, Amines, Alcohols, Copper alloys.	

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
4,4-Methylenediphenyl diisocyanate	TWA: 0.005 ppm	Ceiling: 0.02 ppm	IDLH: 75 mg/m ³
101-68-8		Ceiling: 0.2 mg/m ³	Ceiling: 0.020 ppm 10 min

	Ceiling: 0.2 mg/m ³	10 min
	TWA: 0.005 p	pm
	TWA: 0.05 mg	j/m ³
ACGIH TLV: American Conference of	Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupa	tional

Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Appropriate engineering controls

Engineering Measures	Showers Eyewash stations Ventilation systems
Individual protection measures, su	ch as personal protective equipment
Eye/Face Protection Skin and Body Protection	Tightly fitting safety goggles. Wear protective gloves/clothing. Gloves should be worn. Nitrile rubber gloves showed excellent resistance. Butyl rubber, isoprene and PVC are also effective.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene Measures	Do not eat, drink or smoke when using this product. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Odor	Liquid.	Appearance Odor Threshold	Dark brown. No information available.
Odol	Musty.	Odor Threshold	No information available.
Property	<u>Values</u>	<u>Remarks/ - M</u>	ethod
pH	No data available	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	>300 °C	None known	
Flash Point	230 °C	None known	
Evaporation rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		
Vapor Pressure	No data available	None known	
Vapor Density	No data available	None known	
Relative Density	No data available	None known	
Specific Gravity		None known	
Water Solubility	No data available	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octan		None known	
Autoignition Temperature	No data available	None known	
Decomposition Temperature		None known	
Viscosity	200 mPa @ 20°C	None known	
Flammable Properties	Not flammable		
Explosive Properties	No data available		
Oxidizing Properties	No data available		
. .			
Other information			
VOC Content (%)	No data available		

10. STABILITY AND REACTIVITY

Reactivity	No data available.	
Chemical stability	Stable under recommended storage conditions.	
Possibility of hazardous reactions	None under normal processing.	
Hazardous Polymerization	Contact with moisture, other materials that react with isocyanates, or temperatures above 350°F (177°C), may cause polymerization.	
Conditions to avoid	Protect from moisture. High temperatures.	
Incompatible materials	Water, Strong oxidizing agents, Strong bases, Amines, Alcohols, Copper alloys.	
Hazardous decomposition products Carbon oxides, Nitrogen oxides (NOx), Isocyanates, Isocyanic acid.		

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	
Inhalation	May be harmful if inhaled. May cause irritation of respiratory tract. May cause respiratory sensitization.
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation. May cause sensitization by skin contact.
Ingestion	Ingestion may cause irritation to mucous membranes.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:					
LD50 Oral 7513 mg/kg; Acute toxicity estimate					
Inhalation					
dust/mist	1.2	mg/L; Acute toxicity estimate			

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
4,4-Methylenediphenyl diisocyanate	= 9200 mg/kg (Rat) = 31600	-	= 369 mg/m ³ (Rat)4 h
	mg/kg (Rat)		

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Allergic skin reactions or irritation.

Delayed and immediate effects and also chronic effects from short and long term exposure

Respiratory or Skin Sensitization
Germ Cell Mutagenicity
Carcinogenicity

May cause sensitization by inhalation and skin contact No information available The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Polymethylene		Group 3		
polyphenylene isocyanate				
4,4-Methylenediphenyl		Group 3	-	-
diisocyanate				

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

Reproductive Toxicity STOT - single exposure STOT - repeated exposure Aspiration Hazard

No information available May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Not Classified

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)	
4,4-Methylenediphenyl diisocyanate 101-68-8	NOEC: 1640 mg/l Green algae	LC50: >1000 mg/l (Danio rerio, zebra fish 96 h)		EC50: >1000 mg.l (water flea, Daphnia magna, 24h)	
Persistence and Degrad	ability Not readily b	iodegradable.			
Bioaccumulation	Does not bio	accumulate			
	Chemical Name		Log Pow		
4,4-Methy	lenediphenyl diisocyanate		4.5		
Mobility	No informatio	on available			
Other Adverse Effects	No information	on available.			
	13. DIS	POSAL CONSIDERA	TIONS		
Waste Disposal Methods	Waste Disposal Methods This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. In addition, consult with the appropriate state, regional, or local regulations for additional requirements.				
oontaminateu r aekagin	g Do not to us	e empty containers.			
	14. TR	ANSPORT INFORM	ATION		
Note: This product contains hazardous materials with reportable quantities as listed in Section 1 Based on net weight of product, the shipping description and label may need to be marked with "RQ."					
DOT	Not regulated	Not regulated			
TDG	Not regulated	Not regulated			
MEX	Not regulated	Not regulated			

15. REGULATORY INFORMATION

International Regulations

Ozone depleting substances	Not applicable
Persistent Organic Pollutants	Not applicable
Hazardous Waste	Not applicable
The Rotterdam Convention (Prior	Not applicable

Informed Consent)	
International Convention for the	Not applicable
Prevention of Pollution from Ships	
(MARPOL)	

International Inventories	
TSCA	Complies
DSL/NDSL	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Polymethylene polyphenylene isocyanate	9016-87-9	100	1.0
4,4-Methylenediphenyl diisocyanate	101-68-8	60	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
4,4-Methylenediphenyl diisocyanate	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Polymethylene polyphenylene isocyanate	Х				
4,4-Methylenediphenyl diisocyanate	Х	Х	Х	Х	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION					
NFPA	Health Hazard	2	Flammability 1	Instability 1	Physical and Chemical Hazards -
HMIS_	Health Hazard	2*	Flammability 1	Physical Hazard 1	Personal Protection X

*Indicates a chronic health hazard.

Prepared By

Issuing Date
Revision Date
Revision Note

LifeLast. Inc. 3813 Helios Way Suite 190 Pflugerville, TX 78660 Telephone number: 512-628-2112 19-Mar-2018 16-May-2018 LifeLast updates

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. End of Safety Data Sheet